

单锅逆流混料机系列

Single-pot Counter-flow Mixing Machines



主要用于陶瓷结合剂固结磨具成型料混制。采用逆流混料方式和特殊的拨叉结构,可以快速、均匀的完成混料。

Mainly used in the mixing of vitrified bond abrasive materials. The counter-flow mixing method and the special fork structure can be used to complete the mixing quickly and evenly.

1. 料锅容积 90-400L;
2. 搅拌叉转速范围: 0-80 r/min
3. 锅转速范围: 0-50 r/min
4. 可根据客户要求定制 (防护网、震动筛等)
1. The volume of the pot is 90-400L;
2. Range of mixing fork speed: 0-80 r/min
3. Range of pot speed: 0-50 r/min
4. Can be customized according to customer requirements (protective nets, vibrating screens, etc.)

双锅逆流混料机系列

Double-pot Counter-flow Mixing Machines



主要用于树脂结合剂固结磨具成型料混制。采用双锅结构设计,可以快速、均匀的完成混料。
Mainly used in the mixing of resin bond abrasive materials. The double pot structure can be used to complete the mixing quickly and evenly.

技术参数:

1. 料锅容积 90-400L;
2. 搅拌叉转速范围: 0-80 r/min
3. 锅转速范围: 0-50 r/min
4. 可根据客户要求定制 (防护网、震动筛等)

Technical Data:

1. The volume of the pot is 90-400L;
2. Range of mixing fork speed: 0-80 r/min
3. Range of pot speed: 0-50 r/min
4. Can be customized according to customer requirements (protective nets, vibrating screens, etc.)