

## 石油管螺纹配套刀具

### Petroleum Pipe Thread Matching Tool

GY03材质具有很高的耐磨性和韧性，可用于耐热钢、高锰钢、不锈钢等难加工材料及一般钢材、铸铁和有色金属的半精加工和精加工。特别适合于生产管加工配套刀片，可以搭配CVD/PVD涂层使用。

GY53材质具有良好的抗冲击性能和高温性能，适合于钢材的加工。搭配特别优选的双色CVD复合涂层后，具有卓越的韧性和耐磨性。






GY03 shows high wear resistance and tenacity and can be used for heat-resistant steel, stainless steel and other difficult-to-machine materials. Also, it applies in semi-finish and finish machining of general purpose steel, cast iron and non-ferrous metals etc. It is especially suitable for tube end machining.

GY53 demonstrates great impact resistance and high temperature resistance performance and is suitable for steel machining.

Combined with our special CVD composite coating, it shows excellent tenacity and wear resistance.

型 号	尺 寸 (mm)				牌 号	
	d	s	d1	m	GY0350	GY5350
C/26417	25	6.35	5	1.73	●	○

型 号	尺 寸 (mm)			牌 号		
	L1	L2	s	GY5231	GY7431	
C/26419	25.5	18	4.05	●	○	

<div></div>								
型 号	尺 寸 (mm)						牌 号	
	L1	L2	L3	s	d1	r	GY0350	GY5350
C/32246B/T	25	16.25	7.7	7.94	5.5	1.5	●	○